PPE4.L Lite electronic





4 in**1**

kW

Most important advantages

Electronic control

- energy and water savings through smooth power modulation
- maintaining a constant water temperature of 52°C
- water temperature regulation directly in the faucet by mixing in cold water.
- 4 power levels in one water heater
- option to select maximum power (except for 27 kW model)
- Possibility of reheating preheated water
- Water temperature up to 60°C on the supply
- Easy replacement of the old heater with a new one
- specially designed PPE4 housing equipped with a unique hanger allows for easy installation of the heater in the place of the old one.


Applications




from 9kW from 12kW from 18kW



Dimensions





The special hanger facilitates the installation of PPE4 in the place of the old heater of any brand.

inlet and outlet section G 1/2"

cold water inlet \cap

hot water inlet

electric cable connection point

$oldsymbol{0}$ 52°C

Water heaters with electronic control.

Techn	ical	data
ICCIIII	icai	uala

Туре	Rated power / Rated voltage	Supply water pressure (MPa)	Rated current (A)	Min. connecting wires section mm ²)	Efficiency (∆t=30°) (I/min.)
PPE4.L-10/11/12/15	10/11/12/15 kW / 400V 3~	0,1 - 1,0	3x14,5/15,9/17,3/21,7	4 x 2,5	4,3/5,2/5,8/7,2
PPE4.L-17/18/21/24	17/18/21/24 kW / 400V 3~	0,1 - 1,0	3x24,7/26,0/30,3/34,6	4 x 6	8,1/8,7/10,1/11,6
PPE4.L-27	27 kW / 400V 3~	0,1 - 1,0	3x39	4 x 6	13,0

